## **CUYAHOGA FALLS FIRE DEPARTMENT**

1924 Front Street Cuyahoga Falls, OH 44221 330-971-8400

## PUBLIC EVENT VENDOR SAFETYCHECK LIST (rev 9/2015) ALL VENDORS ARE TO COMPLETE THIS FORM PRIOR TO THE 3:00 FIRE SAFETY INSPECTION

Da	te: _		Event:			
Ve	ndor	bus	siness name:			
Vendor signature:				<b>Type of Vendor:</b> □ Food/Drink □ Novelties □ Personal-		
(Si	gnatu	ire ii	ndicates vendor will comply with the below listed items)	Services/Products □ Charitable Orgs. □ Promotion /advertising		
of t	he e	vent-		g safety checklist is to <b>be reviewed by the vendor</b> and a representative tent. The Fire Inspector will then review all items that apply from this the event opens (around 3:00 PM unless otherwise noted).		
			omply with these safety regulations will be cause for the corm to the fire official upon inspection prior to the even	e vendor to leave the event. The vendor is required to present this nt starting.		
Vor	dore	who	o are cooking:			
V €1			me devices are not permitted to be located under tents or tent like	e assemblies.		
	A 3-A:40-B:C (5lbs ABC) extinguisher is present, fully charged, and has a current annual inspection tag by an authorized extinguisher agency. Cooking operations utilizing oil such as in frying or dipping are additionally required to have a <b>Class K</b> wet chemical extinguisher extinguisher. Cooking operations utilizing solid fuels are additionally required to have a <b>2-A rated water type</b> extinguisher or <b>Class K</b> wet chemical extinguisher.					
		The extinguisher(s) is (are) in plain view and accessible (they are not to be located in cabinets or otherwise hidden from view).				
	Cooking source:					
	□ Charcoal:					
			Is being used in an approved container and is secured so as to p. Is located away from tents and propane sources.	revent tipping.		
			Coals are to be placed in barrels (as provided) at the end of each	n evening		
		_	Only approved charcoal lighter fluid is permitted for starting an			
	Propane:			F		
			Propane cylinders shall exhibit evidence they no older than 12-y 180.205(d) and 180.209.	years of age or have been requalified in accordance with DOT 49 CFR §		
			Cylinders are secured to a non-movable structure. Cylinders are reviewed by the fire official if other means of securing is not po Cylinders are located away from open flame devices.	e <b>not</b> to be tied to tent posts. (Cylinders may be placed in milk crates and ossible).		
				g a soapy water solution. This is to be done every time a cylinder is changed. re in place.		
			Hoses and fittings have been inspected and are free of damage.			
			CYLINDERS ARE NOT TO BE STORED INSIDE TRAIL	ERS OR TRUCKS EITHER ON OR OFF THE FESTIVAL SITE.		
	ctrica		wandad alwaa aa ta ha wad			
			ounded plugs are to be used. no open or frayed wiring.			
		I's are not bypassed.				
		stension cords are of an approved size for the load, are grounded, and are approved for <b>outdoor use</b> .				
		Only fused multi-plug strips are permitted.				
		All connections are weather sealed and off the ground.				
All electrical cords exposed to foot traffic are protected utilizing approved bridging (duct tape does not qualify).			d bridging (duct tape does not qualify).			
			rators are grounded utilizing grounding rods and wiring.			
			d means of egress:	o not normitted to meeting into this once. This includes exprises.) Fire		
A 20-foot fire lane is present down the center of the mall area (vendors are not permitted to protrude into this area. This in department access is provided to all other lot areas. Areas of Emergency Overflow are defined (see map) no vendors or ve				-		
Fire hydrants are not blocked and are accessible. Minimum of 10 feet on all sides.						
		•	does not block the means of egress to existing buildings or other			
Ter	ıts, ca	anop	ies, and pop-ups, membrane structures (including air-inflated	l, air-supported, and frame or cable-supported membranes):		
	At l	east	s or membrane structures having an area in excess of 400 sqft shall received prior approval and a permit from the fire code official.  east one (1) fire extinguishers with an minimum 3-A:40-B:C rating (5lbs ABC) is present and visible (quantity for public assembly tents will be			
				p style tents not equipped with side curtains are exempt from this requirement.		
<ul> <li>An affidavit or affirmation attesting to flame retardency is present or on site for review.</li> <li>Aisles are established and the means of egress maintained.</li> </ul>			ne for review.			
☐ Maximum Occupancy Permitted, EXIT signs, and No Smoking signs are posted (assembly tents only).			nosted (assembly tents only)			
				ency lighting are required at the exits. When sides are present, tent sides at exits		
_			a contrasting color. (OFC-2403.12)(Public assembly tents only)	and required at the emist. Then stood are present, tent stood at exite		
				wn at all corner points sufficiently to prevent lifting in high winds (min. 40lbs		

to 50 lbs per leg). Full, 5-gallon pails of water securely tied to the tent support structure are recommended.

Inflatable signs, portable signs and advertising balloons are prohibited by city ordinance.